

## PRODUCT SPECIFICATION SHEET

# LexTra®

BY FIBERLOK


### Description

Lextra is a unique dimensional flocked graphic product that brings texture to your logo. It reproduces fine details, offers abrasion resistance, withstands 50+ washes for durability and delivers accurate color matching. Our 3D and 4D variants add fabric backing in single color or multi-color. The product is light-weight, flexible and applies in 20 seconds or less.

### Options

Flock Colors: Up to 6 flock colors Pantone matched  
Textile Colors: Unlimited colors Pantone matched


### Lextra® 3D/4D Insert Materials



ObiTex



Satin



Metalweave  
Silver

### Backing

- Heat Transfer - applied with a heat press
- Patch - sew-on (fabric backing)
- PSA (Sticker) - peel and stick
- Velcro - hook side

### Additional Options

- LextraMax - Film-based product for adhesion to difficult substrates

A unique combination of flocked graphics, brilliant colors, fast application, extreme durability and pleasing soft textured surface.

### Best Uses

Lextra is your solution when you want to differentiate your product with a unique look and feel—especially where embroidery can't display small intricate details or when large complex graphics would have high stitch counts. 3D/4D adds more dimensionality and unlimited colors.

## DETAILS

### Minimums

- Order quantity: 250+ (stock colors), 500+ (non-stock)
- For designs greater than 20 square inches, minimums may be less

### Size Specifications Min/Max

- Minimum image size: 1/4" x 1/4" (6.35 mm x 6.35 mm)
- Maximum image size: 25" x 18.8" (635 mm x 477 mm)
- Minimum freestanding line weight: 1.0 mm
- Minimum between freestanding elements: 0.8 mm

### Production Time

- Two (2) days art time
- Order ships two (2) weeks after art approval, or sooner

### Fabrics

Adheres to the following fabrics:

- Canvas • Cotton • Denim • Dri-FIT • Fleece • Mesh
- Polyester • Rayon • Spandex • Textured Knits

Custom fabric testing available

### Testing Information

- 50 home wash cycles with tumble dry at 40° C (104° F)
- Oeko-Tex Standard 100 Certified
- A01 and RSL compliant
- Abrasion resistance per ASTM D3885: 25,000+ cycles
- 25 dry clean cycles

### Shelf Life

Three (3) years in a controlled environment

**Disclaimer:** FiberLok Technologies recommends testing according to your heat press and garment parameters. FiberLok Technologies is not liable for any damages incurred during the application process.

### For More Information:

Main: 970.221.1200  
Fax: 970.221.2424

E-mail: sales@fiberlok.com  
www.fiberlok.com

# FIBERLOK

INNOVATION APPLIED

Rev 20210706