

LexTra®

FLOCK GRAPHICS

Description

LexTra is a unique dimensional flocked graphic product that brings texture to your logo. It reproduces fine details, offers abrasion resistance, withstands 75-100+ washes and delivers accurate color matching.


Our 3D and 4D variants add fabric backing in single color (3D) or multicolor (4D) for a patch-like feel.

This product is lightweight, flexible and applies in 20 seconds or less.

Insert Materials for Lextra® 3D/4D



ObiTex



Satin



Metalweave
Silver

Options

Flock colors: Up to 6 flock colors, Pantone match available

Insert textile colors: unlimited colors, Pantone match available

Backing

- Heat Transfer - applied with a heat press
- Sew-on patch (fabric backing provided)
- Pressure sensitive adhesive (sticker) - peel and stick
- Hook-and-Loop - hook or loop side

Additional Options

- LexTraMax - Film-based product for adhesion to difficult substrates such as neoprene/rubber

A uniquely textured, dimensional graphic delivering brilliant colors, fast application, extreme durability and soft, flexible feel.

Best Uses

Lextra is your solution when you want to differentiate your product with a unique look and feel—especially where embroidery can't display small intricate details or when large complex graphics would have high stitch counts. 3D/4D adds more dimensionality and unlimited colors.

DETAILS

Minimums

- Order quantity: 250+ (stock colors), 500+ (non-stock)
- For designs greater than 20 square inches, minimums may be less

Size Specifications Min/Max

- Minimum image size: 1/4" x 1/4" (6.35 mm x 6.35 mm) / 1/2" x 1/2" 3D/4D
- Maximum image size: 25" x 18.8" (635 mm x 470 mm) / 16" x 14" 3D/4D
- Minimum freestanding line weight: 1.0 mm
- Minimum between freestanding elements: 0.8 mm

Production Time

- Two (2) days art time
- Order ships two (2) weeks after art approval, or sooner

Fabrics

Adheres to the following fabrics:

- Canvas • Cotton • Denim • Dri-FIT • Fleece • Mesh
- Polyester • Rayon • Spandex • Textured Knits

Custom fabric testing available

Testing Information

- 100 home wash cycles with tumble dry at 40° C (104° F) - 75 for 3D/4D
- Oeko-Tex Standard 100 Certified-18.HUS.54 182 Hohenstein HTTI
- A01 and RSL compliant
- Abrasion resistance per ASTM D3885: 25,000+ cycles
- 25 dry clean cycles

Shelf Life

Three (3) years in a controlled environment

Disclaimer: FiberLok Technologies recommends testing according to your heat press and garment parameters. FiberLok Technologies is not liable for any damages incurred during the application process.

For More Information:

Main: 970.221.1200

Fax: 970.221.2424

E-mail: sales@fiberlok.com

www.fiberlok.com

FIBERLOK

INNOVATION APPLIED