

TackleKnit®

BY FIBERLOK

A dye-sublimated textile graphic that comes in a variety of textures with endless vibrant color options, providing a substantial upgrade from screen printed or flat transfers.

Description

TackleKnit is a versatile, durable, low-profile, dye-sublimated fabric graphic that comes in a variety of textures to up your logo game. It is more substantial than a screen print or flat transfer without the color limitations and rigidity of embroidery. The product is lightweight, flexible and applies in 20 seconds or less.

Options

Colors - Unlimited colors, Pantone matching available
 Option: 100% recycled polyester as EcoTwill®

TackleKnit® Materials




Base
(Matte)



Satin
(Shiny)



Chevron



EcoTwill*

Backing

- Heat Transfer - applied with a heat press
- Patch/sew-on
- Pressure sensitive adhesive (sticker) - peel and stick
- Hook-and-Loop - hook or loop side

Additional Options

- Freestanding
- Stretch
- Two (2) Layer - mixed media of 2 different fabrics

Best Uses

TackleKnit is your solution when you need to reproduce more than 6 colors, have heavy gradients, or for photo-level reproduction. TackleKnit also has smaller order quantities and quicker turnaround times for fill-in orders.

DETAILS

Minimums

- Order quantity: 125+
- For designs greater than 20 square inches, minimums may be less

Size Specifications Min/Max

- Minimum image size: 1/2" x 1/2" (12.7 mm x 12.7 mm)
- Maximum image size: 23" x 17" (584 mm x 279 mm)
- Freestanding Base/Satin
- Minimum line weight: 1.5 mm
- Minimum between freestanding elements: 0.75 mm

Production Time

- Two (2) days art time
- Order ships two (2) weeks after art approval, or sooner
- Fill-in orders ship one (1) week after re-order

Fabrics

- Canvas • Cotton • Denim • Dri-FIT • Fleece • Mesh
- Polyester • Rayon • Spandex • Textured Knits

Custom fabric testing available

Testing Information

- 50 home wash cycles with tumble dry at (40° C) 104°F
- Oeko-Tex Standard 100 Certified -18.HUS.54 182 Hohenstein HTTI
- A01 and RSL compliant
- Abrasion resistance per ASTM D3885: 25,000+ cycles
- 25 dry clean cycles

Shelf Life

Three (3) years in a controlled environment

For More Information:

Main: 970.221.1200
 Fax: 970.221.2424

E-mail: sales@fiberlok.com
 www.fiberlok.com